





# **The Profitable Source** for Finishing Products

# Gfp 563TH-3 MaxPro

**Maximum Productivity** 

Top Heat Laminator

Rugged Design
Professional Quality
Proven Performance
Economically Priced

What's the best way to make your production even better?
Shorten film loading time? Make fewer film changes?
Increase throughput speed? The 563TH-3 does all that and more.

#### **563TH-3**

# MAXIMUM PRODUCTIVITY 50% faster throughput FAST ROLL CHANGES

Front/Rear Swing-out shafts

**EASY LOADING** 

3" Aluminum Quick-Grip shifts

RUGGED DESIGN

Metal Alloy heaters

VERSATILE

Roll-to-Roll capability



## overlamination • mounting • board pre-coating

### Spend less time on set-ups and changeovers with swing-out supply shafts.

50% faster throughput and quick application changes save time, effort and money.



- Swing-out Quick-Grip supply shafts
- Drop-in Quick-Grip rewind shafts
- Photoelectric eye for safety
- Optional motorized rear rewind
- Swing-up feed table & 38" output height
- Metal Alloy heater reduces breakage
- 4.5" diameter rollers
- Roller gap measurement scale
- Feed tray safety lock



Motorized rear rewind for roll-to-roll applications



563TH-3

Swing out shafts for faster film changes

#### **APPLICATIONS**

Signs
Banners
POP Displays
Trade show displays
Graphic mounting
Photo mounting
Dry-erase boards
Floor graphics
Window graphics
Vehicle graphics

cTUVus Safety Approval



### Warranty:

1 year parts & labor. *Installation is available.* 

	303111-3
Laminating Width	63"
Roller Diameter	4.5"
Roller Gap	1"
Rear rewind	Optional
Maximum temperature	122°F
Laminating speed	0-20 ft/min
Pressure adjustment	Hand Wheel
Heat method	Metal Alloy heater
Max. roll diameter	8" OD (top); 16" OD (bottom)
Supply Shafts	2 Swing-out
Tension Adjustment	Single knob
Power Supply	110v 12A
Power Consumption	1320W
Foot Pedal	Included
Stand with casters	Included
Net Weight w/ stand	502 lbs.
Dimensions	82" x 28.5" x 50"
Machine Shipping	530bs.; 89.4" x 33.1" x 29.2"
Stand Shipping	143 lbs.; 75" x 33" x 5.8"

Your local dealer is:





## www.AirMark.com

Superior Customer Support & Product Reliability