

Embrace new possibilities with outstanding quality—easily



\*Product image may differ from actual product

### POSSIBILITIES—Level up your offering

- Produce a wide range of signage and décor jobs including applications with thin film and papers.
- Deliver stunning prints with vivid colors, smooth gradients, and sharp text at 150 ft<sup>2</sup>/hr.<sup>1</sup>
- Simple finishing, lamination, and installation with flexible inks and prints that come out dry.

### EFFORTLESS—Get it done quickly and easily

- Find peace of mind with automatic maintenance processes and user-replaceable printheads.
- Save space and time with fast and automated frontloading system.
- Easily reprint projects with job storage in the printer up to 10 GB.
- Monitor your printer from anywhere and expand your capabilities with the cloud-based HP PrintOS app.

### GO BEYOND—Lead with environmental certifications<sup>2</sup>

- Contribute to a comfortable<sup>3</sup> working environment with water-based HP Latex Ink technology.
- Differentiate your business with environmental certifications<sup>2</sup>—including UL ECOLOGO<sup>®4</sup> and EPEAT<sup>5</sup>.
- Access the most sensitive spaces with odorless prints<sup>6</sup> and compatibility with a wide range of alternative substrates.<sup>7</sup>
- Reduce your plastics consumption with carton-based cartridge<sup>8</sup> and labelless supplies; free recycling via HP Planet Partners.<sup>9</sup>

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: <http://www.hp.com/learn/ds>

### Messaging Footnotes

<sup>1</sup> Standard mode (Generic SAV Calendar) 6-pass, 6 colors, 110% ink density. Based on internal HP testing on MACTAC JT 8500 WG-PG. Print speed may vary due to the adaptive printing mechanism, which is designed to avoid image quality defects.  
<sup>2</sup> Based on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product data sheets for more information at <http://hp.com/go/latex>  
<sup>3</sup> Based on odor sensory evaluation when printing with the HP Latex 630 series printer and Mimaki UJV 100-160. Tests done in a 57 sqm room with 5ACH. Test conducted by Odournet following the standard VDI3882, where the HP Latex 630 series air quality were characterized, when Printing, as "neutral" for hedonic tone compared to the Mimaki UJV 100-160.  
<sup>4</sup> UL ECOLOGO<sup>®</sup> Certified HP 832 Latex inks meet a range of stringent human health and environmental considerations. For certifications, see <http://www.ul.com/EL> and <http://www.ul.com/gg>  
<sup>5</sup> Applicable to select HP Latex printers. EPEAT registered where applicable/supported. See <http://epeat.net> for registration status by country.  
<sup>6</sup> Applicable to HP Latex Inks. Based on sensory evaluations conducted by Odournet, done according to VDI Guideline 3882 where 832 and 873 inks were characterized as "weak" in odor intensity and "neutral" for hedonic tone. There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.  
<sup>7</sup> HP applications experts have evaluated the catalog of media listed in the HP Media Locator based on internal criteria to identify those that provide alternative solutions with certain environmental benefits compared to the typical media within the same application type. The information in media locator is provided by the media substrate vendors. HP is not responsible for the veracity of the information from third-party companies published on the HP website. See <http://www.hp.com/go/mediasolutionslocator>  
<sup>8</sup> Applicable to HP 832. Plastic reduction based on moving from plastic ink cartridge to cardboard ink cartridges, with annual manufacturing saving of 33 tons of plastic based on average units of HP 831 and HP 831A ink cartridges from 2018 to 2020.  
<sup>9</sup> Program availability varies. For details, see <http://hp.com/hprecycle>

For more information, please visit <https://www.hp.com/go/latex-630> Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at <https://lkc.hp.com/>



# Technical specifications

<b>Print</b>		<b>Product</b>	102.5 x 33.2 x 55.3 in
<b>Print speed</b>	377 ft <sup>2</sup> /hr - Max Speed (2-pass); 194 ft <sup>2</sup> /hr - Speed (4-pass); 151 ft <sup>2</sup> /hr - Standard (6-pass); 118 ft <sup>2</sup> /hr - Quality (8-pass); 83 ft <sup>2</sup> /hr - High Saturation (12-pass); 71 ft <sup>2</sup> /hr - Standard for Backlits and Textiles (14-pass) <sup>1</sup>	<b>Shipping</b>	110.2 x 44.5 x 50 in
<b>Print resolution</b>	Up to 1200 x 1200 dpi	<b>Operating area</b>	110 x 82.7 in
<b>Technology</b>	HP Latex Printing Technologies	<b>Weight</b>	
<b>Ink types</b>	Water-based HP Latex Inks	<b>Product</b>	507 lb
<b>Ink cartridges</b>	8 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Latex Overcoat)	<b>Shipping</b>	765 lb
<b>Cartridge size</b>	1L	<b>Included</b>	
<b>Printheads</b>	5 (1 cyan/black, 1 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer, 1 HP Latex Overcoat)	<b>What's in the box</b>	HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAI Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor
<b>Long-term print-to-print repeatability</b>	95% of colors < 3 dE2000 <sup>2</sup>	<b>HP Software and solutions</b>	HP PrintOS (PrintBeat, Configuration Center, HP Learn). Explore PrintOS premium software solutions within Professional Print Service Plans.
<b>Media</b>		<b>Environmental ranges</b>	
<b>Applications</b>	Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoor posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics	<b>Operating temperature</b>	59 to 86°F
<b>Handling</b>	Roll feed, take-up reel, automatic horizontal cutter (for vinyl, banner and canvas <sup>3</sup> , paper-based media, and film)	<b>Operating humidity</b>	20 to 80% RH (non-condensing)
<b>Maximum media width</b>	64 in	<b>Acoustics</b>	
<b>Media rolls</b>	1	<b>Sound pressure</b>	Printing: 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
<b>Roll size</b>	18 to 64-in rolls (23 to 64-in rolls with full support)	<b>Sound power</b>	Printing: 7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep) H
<b>Maximum roll weight</b>	92.6 lb	<b>Power</b>	
<b>Maximum roll diameter</b>	9.8 in	<b>Consumption</b>	14-21 kW (2.9 kW peak) (average printing), 85 W (ready), <2.5 W <sup>4</sup> (sleep) (<14 W <sup>5</sup> with DFE), 0.25 W (off)
<b>Thickness</b>	Up to 19.7 mil	<b>Requirements</b>	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord
<b>Media types</b>	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvases, synthetics, (fabrics, mesh, textiles, and any other porous materials require a liner)	<b>Certifications &amp; Compliance</b>	
<b>Connectivity</b>		<b>Safety</b>	IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC)
<b>Interfaces</b>	Gigabit Ethernet (1000Base-T)	<b>Electromagnetic</b>	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)
<b>Dimensions (W x D x H)</b>		<b>Environmental</b>	ENERGY STAR®, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, UL GREENGUARD Gold, UL ECOLOGO
		<b>Warranty</b>	One-year limited hardware warranty

## Ordering information

<b>Product</b>			
171S2A	HP Latex 630 Printer		
Country of origin	Malaysia(B19, B1K, AKV, AC4, ABG, BCD); Singapore(B19)		
<b>Accessories</b>			
171K8A	HP Latex 630 Output Platen Protector Accessory	421S3A	HP Latex Substrate Saver Accessory
21V10A	HP Latex 600/700/800 Series User Maintenance Kit	7HR19A	HP Latex Substrate Loading Accessory
<b>Original HP printing supplies</b>			
4UU94A	HP 836 Optimizer Latex Printhead	4UV79A	HP 832 1-liter Light Cyan Latex Ink Cartridge
4UU95A	HP 836 Universal Latex Printhead	4UV80A	HP 832 1-liter Light Magenta Latex Ink Cartridge
4UV75A	HP 832 1-liter Black Latex Ink Cartridge	4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge
4UV76A	HP 832 1-liter Cyan Latex Ink Cartridge	4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge
4UV77A	HP 832 1-liter Magenta Latex Ink Cartridge	9T062A	HP 833 Latex Maintenance Cartridge
4UV78A	HP 832 1-liter Yellow Latex Ink Cartridge	9T064A	HP 833/838 Latex Ink Collection Unit (2-unit pack)

Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit <https://hp.com/go/OriginalHPInks>

**Original HP large format printing materials**

HP Recycled<sup>6</sup> Removable Adhesive Fabric, 3-in Core (Latex/solvent): REACH compliant<sup>7</sup>  
 HP Recycled<sup>6</sup> Satin Canvas, 3-in Core (Latex/solvent): REACH compliant<sup>7</sup>  
 HP Premium Poster Paper: FSC<sup>8</sup> certified<sup>9</sup>  
 HP PVC-free<sup>10</sup> Wall Paper: UL GREENGUARD GOLD Certified<sup>11</sup>, FSC<sup>8</sup> certified<sup>9</sup>, meets AgBB criteria<sup>12</sup>  
 HP Permanent Gloss Adhesive Vinyl: REACH compliant<sup>7</sup>  
 HP Prime Gloss Air GP: REACH compliant<sup>7</sup>

For the entire HP Large Format Printing Materials portfolio, please see [HPLFMedia.com](http://HPLFMedia.com).

<b>Service and Support</b>	
U60QHE	HP 2 year Plus Service Plan Hardware Support w/DMR
U60QJE	HP 3 year Plus Service Plan Hardware Support w/DMR
U60QLE	HP 5 year Plus Service Plan Hardware Support w/DMR
U60QMPE	HP 1 year Post Warranty Plus Service Plan Hardware Support w/DMR
U60QNPE	HP 2 year Post Warranty Plus Service Plan Hardware Support w/DMR
HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit <a href="http://www.hp.com/go/cpc">http://www.hp.com/go/cpc</a>	

## Specification Footnotes

- Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects. Print mode names may vary depending on the media or application.
- The color variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 3 dE2000. Backlit substrates measured in transmission mode may yield different results.
- Automatic horizontal cutter is for use with thinner banners and canvases only. It is recommended to perform a test.
- Excluding Type 2 DFE (Digital Front End) as defined in Energy Star<sup>®</sup> Product Specification for Imaging Equipment version 3.1.
- Total power measured in sleep mode including the Digital Front End contained on the product.
- Product consists of PET fabric and coatings. With liner attached, 72% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin.
- As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at HP Printing Products and Consumable Supplies.
- 62% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin. Certified according to Global Recycled Standard (GRS) Version 3.0, March 2017.
- Trademark license code FSC-C115319.
- Chemical analysis demonstrated elemental chlorine to be below 200 ppm. Presence of chlorine is attributed to residual chlorine used in the papermaking process, and not due to the presence of PVC.
- HP PVC-free Wall Paper printed with HP Latex Inks is UL GREENGUARD GOLD Certified. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <http://ul.com/gg>
- With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See <http://umweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building>

© Copyright 2026 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

us-en April 2026

